

Technical document · 2024

PREMIUM+ 2500 ARC

Proven technology, exquisite design – elevating your outdoor area with cozy heat.
Easy heat control via the 3-step heat regulation and the included remote control.


Effect	3-step remote dimming: 0, 700, 1500, up to 2500 watts
Heating capacity, TÜV certified*	<i>Heat Zone:</i> Minimum 8 m ² . <i>Comfort Zone:</i> Up to 15 m ² . <i>Maximum Zone:</i> Up to 19 m ²
Technology	Solamagic HeLeN Low-glare® technology
Heating element	Solamagic Solastar Low-glare® heating element
Reflector	Solamagic asymmetric reflektor
Residual light emission	70-75 LUX/KW
Compliance standards	IEC/EN 60335-1, CE
IP rating	IPX4/X5
Safety classification	SK I
Certifications	TÜV-approved: Quality assured in products
Material	Coated aluminium and stainless steel
Front grid	Polished high-grade stainless steel finish
Surface treatment	Powder-coated with corrosion primer base, compliant with EN-ISO 6270-0 standard
Colours	Jet-black, Anthracite dark-gray, Titanium light-gray or Pure-white
Weight	5.15 kg
Connector cable	High-quality silicon-based cable, Hirschmann connector, 2.5 m standard (5/7.5/10m optional), Schuko plug, grounded, UV-resistant
Power supply	230 v / 50 hz
Ampere usage	8.8 amp on 230 v. For optimal performance, use a 10 amp minimum, 13 amp recommended
Installation	Wall or ceiling: Versatile, efficient heating solutions
Recommended mounting height	1.8 – 2.6 meter
Remote control	Yes, included
Garanty	2 years
Dimensions: L – Length: 86.6 cm D – Depth: 20.0 cm H1 – Height: 9.2 cm H2 – Height incl. standard fittings: 21.7 cm Angle: +0/-45°	

*For more information about heating capacity see www.27degreesbyssa.com


Contact:
 info@ssa-ab.com
 Tel DK: 38 414 500
 Tel SE: 010-777 02 50

Safety distances

Wall mounting




Ceiling mounting



Heating capacity at 2500 watts

Test features	Heat Zone	Comfort Zone	Max. Zone
Mouting height	2.6 meter	2.6 meter	2.6 meter
Air temp., start	11 C°	16 C°	19 C°
Heat zone	21 C° +/-0.5	21 C° +/-0,5	21 C° +/-0,5
Windspeed	3 m/sec.	3 m/sec.	0 m/sec.
Capacity	Minimum 8 m²	Up to 15 m²	Up to 19 m²



For more information about heating capacity see www.27degreesbyssa.com